


RCT 3.9



500mm (W)



81.6mm (D)



500mm (W)

500mm (H)

Specifications

Outdoor Rental LED Display

| | |
|--|--|
| Pixel Pitch (mm) | 3.91 mm |
| Brightness (nit) | 5000 nit |
| Contrast | 3500 : 1 |
| Refresh Rate (Hz) | 3840Hz |
| Gray Scale (bit) | 13 bit ~ 14 bit |
| View Angle (horizontal/vertical) | 140° / 120° |
| IP Grade (Front/Back) | IP 65 / IP 54 |
| Maximum / Average Power Consumption (w/m²) | 520W / 175W |
| Cabinet Size (mm) | 500mm x 500mm x 81.6mm |
| Cabinet Weight (kg) | 7.5 kg |
| Cabinet Material | Die-cast Aluminum |
| Module Dimension (mm) | 250mm x 250mm x 14.6mm |
| Cabinet Resolution (Pixels) | 128 X 128 |
| Pixel Density (Pixels/m²) | 65,536 |
| Input A/C Voltage (V) | 100V ~ 240V |
| Working Temperature | -20°C ~ 50°C |
| Working Humidity | 10% ~ 90% |
| Signal Type (with video processor) | DVI / HDMI |
| Control Distance | Cat5e Lan Cable < 100m Single-Mode Fiber Cable < 10km |