


# RCT1.9-GOB




500mm (W)



81.6mm (D)



500mm (W)




500mm (H)

## Specifications

## Indoor Rental LED Display

<b>Pixel Pitch (mm)</b>	1.95 mm
<b>Brightness (nit)</b>	650 nit
<b>Contrast</b>	3000 : 1
<b>Refresh Rate (Hz)</b>	3840Hz
<b>Gray Scale (bit)</b>	13 bit ~ 14 bit
<b>View Angle (horizontal/vertical)</b>	140° / 120°
<b>IP Grade (Front/Back)</b>	IP 30 / IP 30
<b>Maximum / Average Power Consumption (w/m<sup>2</sup>)</b>	530W / 180W
<b>Cabinet Size (mm)</b>	500mm x 500mm x 81.6mm
<b>Cabinet Weight (kg)</b>	7.5 kg
<b>Cabinet Material</b>	Die-cast Aluminum
<b>Module Dimension (mm)</b>	250mm x 250mm x 14.6mm
<b>Cabinet Resolution (Pixels)</b>	256 X 256
<b>Pixel Density (Pixels/m<sup>2</sup>)</b>	262,144
<b>Input A/C Voltage (V)</b>	100V ~ 240V
<b>Working Temperature</b>	-10°C ~ 40°C
<b>Working Humidity</b>	10% ~ 60%
<b>Signal Type (with video processor)</b>	DVI / HDMI
<b>Control Distance</b>	Cat5e Lan Cable < 100m Single-Mode Fiber Cable < 10km

# RCT 2.6




500mm (W)



81.6mm (D)



500mm (W)




500mm (H)

## Specifications

## Indoor Rental LED Display

<b>Pixel Pitch (mm)</b>	2.6 mm
<b>Brightness (nit)</b>	700 nit
<b>Contrast</b>	3000 : 1
<b>Refresh Rate (Hz)</b>	3840Hz
<b>Gray Scale (bit)</b>	13 bit ~ 14 bit
<b>View Angle (horizontal/vertical)</b>	140° / 120°
<b>IP Grade (Front/Back)</b>	IP 30 / IP 30
<b>Maximum / Average Power Consumption (w/m<sup>2</sup>)</b>	530W / 170W
<b>Cabinet Size (mm)</b>	500mm x 500mm x 81.6mm
<b>Cabinet Weight (kg)</b>	7.5 kg
<b>Cabinet Material</b>	Die-cast Aluminum
<b>Module Dimension (mm)</b>	250mm x 250mm x 14.6mm
<b>Cabinet Resolution (Pixels)</b>	192 X 192
<b>Pixel Density (Pixels/m<sup>2</sup>)</b>	147,456
<b>Input A/C Voltage (V)</b>	100V ~ 240V
<b>Working Temperature</b>	-10°C ~ 40°C
<b>Working Humidity</b>	10% ~ 60%
<b>Signal Type (with video processor)</b>	DVI / HDMI
<b>Control Distance</b>	Cat5e Lan Cable < 100m Single-Mode Fiber Cable < 10km

# RCT 3.9




500mm (W)



81.6mm (D)



500mm (W)




500mm (H)

## Specifications

## Outdoor Rental LED Display

Pixel Pitch (mm)	3.91 mm
Brightness (nit)	5000 nit
Contrast	3500 : 1
Refresh Rate (Hz)	3840Hz
Gray Scale (bit)	13 bit ~ 14 bit
View Angle (horizontal/vertical)	140° / 120°
IP Grade (Front/Back)	IP 65 / IP 54
Maximum / Average Power Consumption (w/m <sup>2</sup> )	520W / 175W
Cabinet Size (mm)	500mm x 500mm x 81.6mm
Cabinet Weight (kg)	7.5 kg
Cabinet Material	Die-cast Aluminum
Module Dimension (mm)	250mm x 250mm x 14.6mm
Cabinet Resolution (Pixels)	128 X 128
Pixel Density (Pixels/m <sup>2</sup> )	65,536
Input A/C Voltage (V)	100V ~ 240V
Working Temperature	-20°C ~ 50°C
Working Humidity	10% ~ 90%
Signal Type (with video processor)	DVI / HDMI
Control Distance	Cat5e Lan Cable < 100m Single-Mode Fiber Cable < 10km

# RCW 2.9




500mm (W)



81.6mm (D)



500mm (W)




500mm (H)

## Specifications

## Outdoor Rental LED Display

Pixel Pitch (mm)	2.97 mm
Brightness (nit)	4000 nit
Contrast	4000 : 1
Refresh Rate (Hz)	3840Hz
Gray Scale (bit)	13 bit ~ 14 bit
View Angle (horizontal/vertical)	140° / 120°
IP Grade (Front/Back)	IP 65 / IP 54
Maximum / Average Power Consumption (w/m <sup>2</sup> )	670W / 225W
Cabinet Size (mm)	500mm x 500mm x 81.6mm
Cabinet Weight (kg)	7.5 kg
Cabinet Material	Die-cast Aluminum
Module Dimension (mm)	250mm x 250mm x 14.6mm
Cabinet Resolution (Pixels)	168 X 168
Pixel Density (Pixels/m <sup>2</sup> )	112,896
Input A/C Voltage (V)	100V ~ 240V
Working Temperature	-20°C ~ 50°C
Working Humidity	10% ~ 90%
Signal Type (with video processor)	DVI / HDMI
Control Distance	Cat5e Lan Cable < 100m Single-Mode Fiber Cable < 10km

# RCW 3.9



500mm (W)



81.6mm (D)



500mm (H)



500mm (W)

## Specifications

## Outdoor Rental LED Display

<b>Pixel Pitch (mm)</b>	3.91 mm
<b>Brightness (nit)</b>	3800 nit
<b>Contrast</b>	5000 : 1
<b>Refresh Rate (Hz)</b>	3840Hz
<b>Gray Scale (bit)</b>	13 bit ~ 14 bit
<b>View Angle (horizontal/vertical)</b>	140° / 120°
<b>IP Grade (Front/Back)</b>	IP 65 / IP 54
<b>Maximum / Average Power Consumption (w/m<sup>2</sup>)</b>	740W / 245W
<b>Cabinet Size (mm)</b>	500mm x 500mm x 81.6mm
<b>Cabinet Weight (kg)</b>	7.5 kg
<b>Cabinet Material</b>	Die-cast Aluminum
<b>Module Dimension (mm)</b>	250mm x 250mm x 14.6mm
<b>Cabinet Resolution (Pixels)</b>	128 X 128
<b>Pixel Density (Pixels/m<sup>2</sup>)</b>	65,536
<b>Input A/C Voltage (V)</b>	100V ~ 240V
<b>Working Temperature</b>	-20°C ~ 50°C
<b>Working Humidity</b>	10% ~ 90%
<b>Signal Type (with video processor)</b>	DVI / HDMI
<b>Control Distance</b>	Cat5e Lan Cable < 100m Single-Mode Fiber Cable < 10km